

TIGHTENING TORQUES : ROAD WHEELS

1. recommendations

CAUTION : The use of impact wrenches to refit the wheel bolts and wheel anti-theft bolts is strictly prohibited.

Ensure that the anti-theft wrench is positioned correctly on refitting.

CAUTION : Tighten the wheel bolts using a torque wrench.

2. Steel and alloy wheel tightening torques

vehicles	Steel rims	aluminium rims
C ZERO	9,8 daNm	
C1	10 daNm	
C2	9 daNm	
C3		
C3 Pluriel		
C3 (A51)	11 daNm	
DS3	11 daNm	
C3 PICASSO	11 daNm	
C3 AIRCROSS	11 daNm	
C4	9 daNm	10 daNm
C4 PICASSO	10 daNm	
B7	10 daNm	
XSARA PICASSO	9 daNm	10 daNm
C5 (X3 X4)	10 daNm	9 daNm
C5 (X7) (XW)	11 daNm	9 daNm
C6	-	9 daNm
C8	10 daNm	
C CROSSER	10 daNm	
C15	8 daNm	
NEMO	8,6 daNm	9,8 daNm
BERLINGO (M49 ,M59)	9 daNm	
BERLINGO (B9)	11 daNm	9 daNm
DISPATCH	10 daNm	9 daNm
RELAY (ALL TYPES - Wheel 15")	16 daNm	
RELAY (ALL TYPES - Wheel 16")	18 daNm	